

Wall mounted unit

ATX-KV



Siesta



Energy saving during standby mode



Online controller via app



Multi model application

Discreet Siesta wall mounted unit providing high efficiency and comfort

- › Whisper quiet in operation down to 20 dBA
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- › Seasonal efficiency values up to A++ in cooling and heating

ATX-KV + ARX-K



Indoor unit		ATX	20KV	25KV	35KV	
Casing	Colour		White			
Dimensions	Unit HeightxWidthxDepth	mm	286x770x225			
Sound power level	Cooling	dB(A)	55		58	
	Heating	dB(A)	55		58	
Sound pressure level	Cooling	High/Low/Silent operation	dB(A)	39/25/20	40/26/20	43/27/20
	Heating	High/Low/Silent operation	dB(A)	39/28/23	40/28/23	43/29/26
Control systems	Infrared remote control		ARC480A11			
	Wired remote control		BRC944B2 / BRC073A1			


Efficiency data		ATX + ARX	20KV + 20K	25KV + 25K	35KV + 35K	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.5/4.0	
Heating capacity	Min./Nom./Max.	kW	1.3/2.5/3.5	1.3/3.0/4.0	1.3/4.0/4.8	
Power input	Cooling	Min./Nom./Max.	kW	0.310/0.504/0.720	0.310/0.661/0.720	0.290/1.020/1.300
	Heating	Min./Nom./Max.	kW	0.250/0.524/0.950	0.250/0.688/0.950	0.290/0.995/1.290
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class		A++		
		Pdesign	kW	2.00	2.50	3.50
		SEER		6.62	6.46	6.42
	Heating (Average climate)	Energy efficiency class		A++		
		Pdesign	kW	2.20	2.40	2.80
		SCOP/A		4.64	4.60	4.62
Nominal efficiency	EER		3.97	3.78	3.43	
		COP		4.77	4.36	4.02
	Annual energy consumption	kWh	252	331	511	
	Energy labeling	Cooling		A		
Directive	Heating		A			

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Outdoor unit		ARX	20K	25K	20K
Dimensions	Unit HeightxWidthxDepth	mm	550x658x275		
Sound power level	Cooling	dB(A)	60		
	Heating	dB(A)	61		
Sound pressure level	Cooling	High	dB(A)		
	Heating	High	dB(A)		
Operation range	Cooling	Ambient	Min.-Max.	°CDB	
	Heating	Ambient	Min.-Max.	°CWB	
Refrigerant	Type/Charge/GWP	kg/TCO ₂ eq	R-410A/0.74/1.5/2.087.5		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN17-037

04/17



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.