



Water cooled
screw chiller,
high efficiency,
standard sound

EWWQ-B-XS

R-410A



Screw compressor

- › 1 or 2 stepless single-screw compressors
- › One or two truly independent refrigerant circuits for outstanding reliability

- › Shell and tube heat exchanger
- › Standard electronic expansion valve
- › Compact design


EWWQ-B-XS



Cooling only				EWWQ-B-XS	420	520	640	730	800	970	C10	C11	C12	C13	C14	C15	C16	C17	C19	C20	C21			
Cooling capacity	Nom.		kW	420	513	636	722	798	969	1,033	1,111	1,153	1,265	1,363	1,442	1,580	1,740	1,870	2,025	2,156				
Power input	Cooling	Nom.	kW	88.7	107	131	149	166	201	213	239	238	262	281	299	324	361	397	436	474				
Capacity control	Method			Stepless																				
	Minimum capacity		%	12.5						25.0	12.5	25.0												
EER				4.74	4.79	4.84	4.83	4.81		4.86	4.64	4.85	4.83	4.85	4.83	4.88	4.81	4.71	4.64	4.55				
ESEER				5.27	5.29	5.37	5.36	5.30	5.09	5.56	4.99	5.52		5.65	5.61	5.26	5.18	4.98	4.91	4.75				
IPLV				6.36		6.45	6.42	6.35	6.06	6.11	5.92	6.06	6.07	6.23	6.19	5.82	5.92	6.03	5.81	5.93				
Dimensions	Unit	Height	mm	2,001				2,003	2,001	2,454	2,003	2,454					2,495							
		Width	mm	1,276		1,268	1,314	1,446	1,350	1,446	2,454					1,350								
		Depth	mm	3,863			3,878	3,920	5,219	3,919	5,219				4,829				4,865					
Weight	Unit		kg	2,322	2,403	2,464	2,738	2,407	2,427	4,775	2,457	4,831	4,873	4,919	4,969	5,117	5,388	5,408	5,414					
	Operation weight		kg	2,594	2,685	2,745	3,158	2,815	3,056	5,431	3,086	5,479	5,512	5,546	5,606	5,794	5,843	6,110	6,118	6,124				
Water heat exchanger - evaporator	Type			Single pass shell and tube																				
	Water volume		l	220	213	200	334	325	538	587	538	575	563	551		495	484	535	527					
Compressor	Water pressure drop	Cooling	Nom.	kPa	55	68	71	64	57	53		68	64	55	67	74	69	88	90	111	124			
	Type				Single screw compressor																			
Sound power level	Cooling	Nom.	dB(A)	1				2		1		2												
				Quantity																				
Sound pressure level	Cooling	Nom.	dB(A)	82	83	84	83	84	86	85	86	87		86	87	88								
Operation range	Evaporator	Cooling	Min.	°CDB										-4										
			Max.	°CDB										10										
	Condenser	Cooling	Min.	°CDB										25										
			Max.	°CDB										45										
Refrigerant	Type/GWP			R-410A/2,087.5																				
	Circuits	Quantity		1				2		1		2												
Refrigerant charge	Per circuit		kg	120.0	130.0	95.0	135.0	110.0	150.0	120.0	130.0	120.0	150.0	120.0	150.0	130.0	150.0							
	Per circuit		TCO ₂ Eq	250.5	271.4	198.3	281.8	229.6	313.1	250.5	271.4	250.5	313.1	250.5	313.1	271.4	313.1							
Piping connections	Evaporator water inlet/outlet		mm	152.4				203.2		254	203.2	254	203.2				254							
	Condenser water inlet/outlet (OD)			-																				
	Condenser water inlet/outlet		inch	8			6			5	6	5		6		8								
Unit	Starting current	Max	A	455				656		626	656	663		690		902	954	988	998					
				Running current	Cooling	Nom.	A	149	173	208	235	258	313	346	370	381	417	443	469	511	567	621	678	734
								Max	A	179	214	259	294	308	372	427	434	473	519	553	587	615	679	744
Power supply	Phase/Frequency/Voltage		Hz/V	3~/50/400																				

Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; entering condenser water temp. 30°C; leaving condenser water temp. 35°C; full load operation. Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-461_2 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.